

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2001006749 A**

(43) Date of publication of application: **12.01.01**

(51) Int. Cl.

H01M 10/40
H01M 4/04
H01M 10/04

(21) Application number: **11179347**

(22) Date of filing: **25.06.99**

(71) Applicant: **TOYOTA CENTRAL RES & DEV
LAB INC TOYOTA MOTOR CORP**

(72) Inventor: **OKUDA NARUAKI
KAWAI YASUAKI
EBINE YOSHIAKI
UKIYOU YOSHIO
SUKIGARA KAZUTOSHI
MIURA FUSAYOSHI
MASAKI HIDEYUKI
KUROYANAGI KOJI**

(54) **LITHIUM SECONDARY BATTERY**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a lithium secondary battery which is stable in battery internal pressure and excellent in safety by facilitating release of gas from an electrode body thus making a safety valve sufficiently function.

SOLUTION: In a lithium secondary battery constituted by providing an electrode body formed by superimposing positive electrode sheets and negative electrode sheets formed by binding electrode laminate materials 12 on a surface of each metallic foil collector in layers via a separator and a safety valve for avoiding an abnormal rise in battery internal pressure and providing a battery case storing the electrode body, at least one of the positive electrode sheet and the negative electrode sheet is provided with a means for facilitating release of generated gas from the electrode body. The means consists of a plurality of small holes 15 and/or slits passing through the collector 11 and the electrode laminate materials 12 and a continuous groove which is formed by binding the

electrode laminate materials 12 thinner than other parts or not binding, and leads to at least one end of the electrode sheets.

COPYRIGHT: (C)2001,JPO

